

TECHNICAL DATA

Burgess Marine Crack Seal

100ml & 100ml Norwegian

PRODUCT DESCRIPTION

Burgess Marine Crackseal is a highly penetrating resin carried by water. It will work its way into the smallest cracks and penetrate wherever water is able to. Water will not stop Crackseal from getting into the crack. It must be allowed to dry to form a tough, flexible seal.

PRODUCT BENEFITS

* Repairs cracks in and gaps in deck caulking, hatches and much more.

PRODUCT USAGE

Seals crack and gaps in wood and plastic. Ideal for leaks in deck caulking, hatches, deck lights, scuttle, deck glands, cracks in low voltage electric and other plastic fittings.

DIRECTIONS FOR USE

Before treatment it may be necessary to block the the underside of the crack using masking tape or putty) to prevent crackseal running right through. Crackseal is unaffected by damp or dust so allow to flow into crack. Before drying wipe away any surplus with a wet cloth. NOTE: If used in conjunction with Burgess Marine Woodsealer always treat cracks with cracksealer AFTER applying woodsealer coating as the woodsealer cannot penetrate cracksealer.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place and protect from frost.

SHELF LIFE

2 years from date of manufacture.

Revision: 1 | Date: 04/05/2012

Appearance : Colourless liquid

Odour : Odourless
Specific Gravity : 1.005

Solubility : Miscible in water



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
100ml	0750	5020618007500
100ml Norwegian	1702	N/A





TECHNICAL DATA

Burgess Marine Crack Seal

100ml & 100ml Norwegian

Flammability : Non flammable

SAFETY PRECAUTIONS

Revision: 1 | Date: 04/05/2012

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

