

Granville Hy-Vis Hydraulic 32

5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hy-vis 32 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603

David Brown: S1.53.101

Denison Filterability: TP021000

DIN: 51524 Part 2

Vickers: 1.286.S & 1.286.S3



* Image for illustrative purposes only.

PRODUCT BENEFITS

*Excellent pumpability

*Protects against oxidation and corrosion.

SIZE	PART NO	BARCODE
5 Litre	0182	5020618001829
20 Litre	0723	5020618007234
199 Litre	0132	5020618001324

STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil



Granville Hy-Vis Hydraulic 32

5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	28.8	35.2	32.57
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s			5.54
Density	ASTM D792	@ 15°C			0.871

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

