

Granville FS-R 5W/30

1 Litre, 5 Litre, 20 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville FS-R 5W/30 is formulated using the very latest advanced additive technology and base oils. Manufactured to meet the latest performance demands of certain Renault vehicles requiring a low SAPs (sulphated ash, phosphorous and sulphur) content. Suitable for engines with diesel particulate filters fitted where this grade and specification is required.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C4

Renault: RN0720

MB: 226.51

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Store Upright and sealed in a cool dry place, out of the reach of children.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0568	5020618005681
5 Litre	0569	5020618005698
20 Litre	0565	5020618005650
205 Litre	0571	5020618005711



Granville FS-R 5W/30

1 Litre, 5 Litre, 20 Litre & 205 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: Less Than 80%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	11.572
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.46
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		11	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			71.05
Density	ASTM D792	@ 15°C			0.851

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

