



Liquid Wrench Silicone Spray

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Liquid Wrench Silicone Spray

Product code 6905

Unique Formula Identifier (UFI) 0JP1-N03T-S00E-7Q89

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)

Intended for general public.

Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer

Company Identification Granville Oil & Chemicals Ltd

Address of Manufacturer 29 Goldthorpe Ind. Est.,

Goldthorpe, Rotherham, South Yorkshire,

Postal code S63 9BL

Telephone: +44 (0)1709 890099

Fax Not known.

E-mail lab@granvilleoil.com

Office hours 08:00 - 17:00

Supplier

Company Identification Veedol Deutschland GmbH
Address of Supplier Hans-Böckler-Straße 10

Langenfeld, Germany

Postal code 40764

Telephone: +49 (0) 2173 893 30 30

Fax Not known.

E-mail lab@granvilleoil.com

Office hours

1.4 Emergency telephone number

Emergency Phone No. +44 (0)1709 890099

Contact Granville Lab

National response centre

Address NHS Direct
Emergency Phone No. +44 111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Page: 1 - 12 Revision: 1 - Replaces:



Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

Regulation (EC) No. 1272/2008 (CLP) Aerosol 1 :Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2: Causes skin irritation.

STOT SE 3: May cause drowsiness or dizziness.

Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP)

Product Name Liquid Wrench Silicone Spray

Contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard Pictogram(s)





Signal Word(s) Danger

Hazard Statement(s) H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s) P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P271: Use only outdoors or in a well-ventilated area.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/

122°F.

Unique Formula Identifier (UFI) 0JP1-N03T-S00E-7Q89

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Page: 2 - 12 Revision: 1 - Replaces:



Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / REACH Registration No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Petroleum gases, liquefied[A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately – 40 °C to 80 °C (– 40 °F to 176 °F).]	68476-85-7	270-704-2	30-50	Flam. Gas 1A H220	GHS02
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		919-857-5		Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H336	GHS02 GHS08 GHS07
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		921-024-6		Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411	GHS02 GHS08 GHS07 GHS09
White mineral oil (petroleum)	8042-47-5	232-455-8	1-10	Asp. Tox. 1 H304	GHS08
Hydrocarbons, C6, isoalkanes, <5% n- hexane	64742-49-0	931-254-9 01- 2119484651- 34	1-10	Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411	GHS02 GHS08 GHS07 GHS09

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation Remove person to fresh air and keep comfortable for breathing.

Skin Contact Wash skin with plenty of water. Take off contaminated clothing. If skin irritation

occurs: Get medical advice/attention.

Eye Contact Rinse eyes with water as a precaution.

Ingestion Call a poison center or a doctor if you feel unwell.



Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. May cause irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media Water spray. Dry powder. Foam. Carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Fire hazard Extremely flammable aerosol.

Explosion hazard Pressurised container: May burst if heated.

Hazardous decomposition products in

case of fire

Toxic fumes may be released.

5.3 Advice for firefighters

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Emergency procedures Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid

breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Protective equipment Do not attempt to take action without suitable protective equipment. For further

information refer to section 8: "Exposure controls/personal protection".

6.2 Environmental precautions

Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Mechanically recover the product.

Other information Dispose of materials or solid residues at an authorized site.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Precautions for safe handling Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid

breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear

personal protective equipment.

Hygiene measures Wash contaminated clothing before reuse. Do not eat, drink or smoke when using

this product. Always wash hands after handling the product.

7.2 Conditions for safe storage, including any incompatibilities



Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool

7.3 Specific end use(s)

Not known.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

Occupational Exposure Limits										
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note				
Liquefied petroleum gas	68476-85-7	1000	1750	1250	2180	(f)				

Region Source

United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes

(f) Carc (only applies if LPG contains more than 0.1% of buta-1,3-diene)

8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and

intrinsically safe electrical systems. Ensure adequate ventilation. A washing

facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment

Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state Aerosol
Colour Pale orange.



Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

Odour Characteristic.

Melting point/freezing point Not known.

Boiling point or initial boiling point and Not applicable.

boiling range

Flammability Extremely flammable aerosol.

Explosive properties Pressurised container: May burst if heated.

Lower and upper explosion limitNot known.Flash Point< 23 °C</td>Auto-ignition temperatureNot known.Decomposition TemperatureNot known.pHNot known.Kinematic ViscosityNot known.

Solubility (Water) : Not known.

Solubility (Other): Not known.

Partition coefficient n-octanol/water (log Not known.

value)

Vapour pressure Not known.

Density and/or relative density Not known.

Relative vapour density Not known.

Particle characteristics Not known.

9.2 Other information

% of flammable ingredients 87.76689424 %

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of

ignition.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Ingestion Calculation method : Not classified.

Acute toxicity - Skin Contact Calculation method : Not classified.

Acute toxicity - Inhalation Calculation method : Not classified.

Skin corrosion/irritation Calculation method : Causes skin irritation.



Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

Serious eye damage/irritation

Calculation method : Not classified.

Skin sensitization data

Calculation method : Not classified.

Respiratory sensitization data

Calculation method : Not classified.

Carcinogenicity

Calculation method : Not classified.

Carcinogenicity

Calculation method : Not classified.

STOT - single exposure Calculation method : May cause drowsiness or dizziness.

STOT - repeated exposure Calculation method : Not classified.

Aspiration hazard Self classification: Not classified.

11.2 Information on other hazards

Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Toxicity - Aquatic invertebrates Not known.

Toxicity - Fish Not known.

Toxicity - Algae Not known.

Toxicity - Sediment Compartment Not classified.

Toxicity - Terrestrial Compartment Not classified.

12.2 Persistence and degradability

Not known.

12.3 Bioaccumulative potential

Not known.

12.4 Mobility in soil

Not known.

12.5 Results of PBT and vPvB assessment

Not known.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of contents in accordance with local, state or national legislation. Send to a licensed recycler, reclaimer or incinerator. Dispose of this material and its container to hazardous or special waste collection point. Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Do not allow to enter drains, sewers or watercourses. Do NOT landfill.

13.2 Additional Information





Liquid Wrench Silicone Spray

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

UN No. 1950

14.2 UN proper shipping name

UN proper shipping name AEROSOLS

14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 2
ADR Classification Code 5F

Special Provisions 190 327 344 625

Limited Quantities 1 L
Excepted Quantities E0

Emergency Action Code

Mixed Packing Instructions for Packages P207 LP200 Special Packing Provisions for Packages PP87 RR6 L2

Mixed Packing Instructions for Packages MP9

Packing Instructions for Portable Tanks
Special Provisions for Portable Tanks

Tank Code for Tanks

Special Provisions for Tanks

Vehicle for Tank Carriage

ADR Transport Category 2
Tunnel Restriction Code D
Special Provisions for Carriage - V14

Packages

Special Provisions for Carriage - Bulk

Special Provisions for Carriage - Loading, CV9 CV12

Unloading and Handling

Special Provisions for Carriage - S2

Operation ADR HIN

IMDG

IMDG Class 2

Special Provisions 190 327 344 625

Limited Quantities 1 L
Excepted Quantities E0

Mixed Packing Instructions for Packages P207 LP200 Special Packing Provisions for Packages PP87 RR6 L2

Packing Instructions for Portable Tanks
Special Provisions for Portable Tanks

IMDG EMS F-D, S-U Stowage and Handling SW1 SW22



Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

SG69 Segregation

Marine Pollutant

ICAO/IATA

IATA Proper Shipping Name **AEROSOLS**

Excepted Quantities E0 Passenger and Cargo Aircraft Limited Y203

Quantities Packing Instructions

Passenger and Cargo Aircraft Limited

Quantities Max net Qty

Passenger and Cargo Aircraft Packing Instructions

Passenger and Cargo Aircraft Max net

Qty Cargo Aircraft Packing Instructions 203

Cargo Aircraft Max net Qty 150Kg

Special Provisions A145, A167, A802

Emergency Response Guidebook (ERG) 10L

Code Labels

Labels



30Kg G

203

75Kg

14.4 Packing group

Packing group

14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Maritime transport in bulk according to IMO instruments

No information available

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very Not listed

High Concern for Authorisation

REACH: ANNEX XIV list of substances Not listed

subject to authorisation

Carcinogens: category 1A (68476-85-7), Mutagens: category 1B (64742-49-0), REACH: Annex XVII Restrictions on the manufacture, placing on the market and Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (),

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (), White use of certain dangerous substances,

mixtures and articles mineral oil (petroleum) (8042-47-5)

Community Rolling Action Plan (CoRAP) Not listed

Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

Regulation (EU) N° 2019/1021 of the

Not listed European Parliament and of the Council

on persistent organic pollutants

Regulation (EC) N° 1005/2009 on Not listed

substances that deplete the ozone layer

Regulation (EU) N° 649/2012 of the Not listed

European Parliament and of the Council concerning the export and import of

hazardous chemicals National regulations

Other Not known.

15.2 Chemical Safety Assessment

A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s)



GHS02



GHS08: GHS: Health hazard GHS09: GHS: Environment

Flam. Gas 1A: Flammable gas Category 1A Hazard classification

Aerosol 1: Aerosol, Category 1

Flam. Liq. 2: Flammable liquid, Category 2 Flam. Liq. 3: Flammable liquid, Category 3 Asp. Tox. 1: Aspiration hazard, Category 1

Skin Irrit. 2: Skin corrosion/irritation, Category 2

STOT SE 3: Specific target organ toxicity — single exposure, Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment, Chronic, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment, Chronic, Category 3

Hazard Statement(s) H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

H229: Pressurised container: May burst if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s)

Acronyms

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P312: Call a POISON CENTRE/doctor if you feel unwell.

P321: Specific treatment (see Medical Advice on this label).

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/

122°F.

P501: Dispose of contents in accordance with local, state or national legislation.

ADN: European Agreement concerning the International Carriage of Dangerous

Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE: Acute Toxicity Estimate **CAS**: Chemical Abstracts Service

CLP: Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substances and mixtures **DNEL**: Derived No Effect Level EC: European Community

EINECS: European Inventory of Existing Commercial Chemical Substances

IATA: International Air Transport Association

IBC: Intermediate Bulk Container

ICAO: International Civil Aviation Organization

Page: 11 - 12

Revision: 1 - Replaces:

Date of Revision: 23-05-2023

Liquid Wrench Silicone Spray

IMDG: International Maritime Dangerous Goods

LTEL: Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic PNEC : Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit STOT : Specific Target Organ Toxicity

UN: United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for Regulation (EC) No. 1272/2008 (CLP) data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Granville Oil & Chemicals Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Granville Oil & Chemicals Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Page: 12 - 12 Revision: 1 - Replaces: