



Granville

FS Motorsport 10W/60

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Granville FS Motorsport 10W/60 uses synthetic additive technology designed to provide optimum performance and protect under the most severe driving conditions. Suitable for use in high performance, competition and modified engines both normally aspirated and turbo charged.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SM/CF
ACEA: A3/B4

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0488	5020618004882
5 Litre	0489	5020618004899





Granville

FS Motorsport 10W/60

1 Litre & 5 Litre

Odour : Characteristic
Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	21.9	<26.1	24.396
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		10.625
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			168.124
Density	ASTM D792	@ 15°C			0.85
Pour Point	ASTM D97	°C		-30	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

