

# Granville Platinum Plus 10W/40

1 Litre, 5 Litre & 20 Litre

## PRODUCT DESCRIPTION

Granville Platinum Plus 10W/40 is a high performance semi synthetic oil suitable for petrol and diesel engines including turbo, fuel injection and those fitted with catalytic converters.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 502.00 & 505.00

ACEA: A3/B4

API: SN/CF

MB: 229.3

Renault: RN0700 & RN0710



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

SIZE	PART NO	BARCODE
1 Litre	0045	5020618000457
5 Litre	0043	5020618000433
20 Litre	0295	5020618002956

## PRODUCT USAGE

For engines where this specification of lubricant is required

## DIRECTIONS FOR USE

As recommended by the engine manufacturer

## STORAGE INSTRUCTIONS

Keep upright and sealed in a cool, dry place out of the reach of children



# Granville Platinum Plus 10W/40

1 Litre, 5 Litre & 20 Litre

## SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: Less than 70%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	13.46
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.25
Pour Point	ASTM D97	°C		-35	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			81.77
Density	ASTM D792	@ 15°C			0.872
Viscosity Index	ASTM D2270				160.96

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

