

Granville Diesel Gold 15W/40

5 Litre

PRODUCT DESCRIPTION

Granville Diesel Gold 15W/40 is a semi-synthetic engine oil for use in older engines requiring a lubricant of this grade.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 505.00 & 502.00

ACEA: A3/B4

API: SN/CF

MB: 229.3



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

| SIZE | PART NO | BARCODE |
|---------|---------|---------------|
| 5 Litre | 0880 | 5020618008804 |

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid



Granville Diesel Gold 15W/40

5 Litre

Odour : Characteristic

Solubility : Insoluble

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 12.5 | <16.3 | |
| Viscosity Index | ASTM D2270 | | 80 | | |
| Viscosity, CCS -20°C | ASTM D4684 | mPa.s | | 7000 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 10 | | |
| Pour Point | ASTM D97 | °C | | -27 | |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.7 | | |
| NOACK Volatility | ASTM D5800 | % | | 13 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

