Granville
More than just an oil company

TECHNICAL DATA

Revision: 3 | Date: 17/07/2023

Granville

Hypalube LX Mineral 10W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube LX 10W/30 is a superior mineral engine oil, formulated to increase engine protection during cold start up thereby reducing engine wear. Hypalube 10W/30 is a low viscosity engine oil that offers improved fuel economy and outstanding engine cleanliness.



* Image for illustrative purposes only.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SL/CF
ACEA: A2/B2 & E2
MB: 229.1
VW: 505.00
Ford: WSS-M2C909-A

SIZE	PART NO	BARCODE
1 Litre	0083	5020618000839
5 Litre	0081	5020618000815
20 Litre	0091	5020618000914
199 Litre	0094	5020618000945

PRODUCT BENEFITS

* Ensures lubricant performance
* Excellent high & low temperature performance
* Suitable for petrol and diesel engines
* Outstanding engine cleanliness and sludge control

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Hypalube LX Mineral 10W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid
Odour : Characteristic
Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	12.2
Viscosity, CCS -25°c	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		12.5
Pour Point	ASTM D97	°c		-30	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			80.5
Density	ASTM D792	@ 15°c			0.86
Viscosity Index	ASTM D2270				147

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com