

TECHNICAL DATA

Granville Blue Gasket Sealant

40g Norwegian

PRODUCT DESCRIPTION

Granville Blue Gasket Sealant is a new technology sealant which is free from the solvent problems of other formulations and stays flexible when cured. Blue Gasket Sealant cures to a non-hardening consistency forming an instant seal that will not crack, chip or flake making it ideal for sealing metal-to-metal joints where a gasket is not required. Use on cylinder heads, sumps, pumps, gearboxes, axles, hydraulic and pneumatic assemblies.

PRODUCT BENEFITS

- * New advanced non-setting formulation
- * Stays flexible
- * Resists petrol, steam, antifreeze, oils, common solvents and most chemicals
- * Methylene Chloride free



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
40g Norwegian	1696	N/A

PRODUCT USAGE

Ideal for sealing metal-to-metal joints where a gasket is not required. Use on cylinder heads, sumps, pumps, gearboxes, axles, hydraulic and pneumatic assemblies.

DIRECTIONS FOR USE

Remove cap from tube and pierce end. Ensure that parts to be fitted are clean, dry and free from oil & grease, apply a continuous bead around the area, leave for 5-10 minutes then join the surfaces together.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place out of direct sunlight and away from sources of heat.

SHELF LIFE

2 years from date of manufacture.

Revision: 2 | Date: 23/05/2013





TECHNICAL DATA

Granville Blue Gasket Sealant

40g Norwegian

SPECIFICATION INFORMATION

Operating Temperature: -50°C to + 150°C

Gap Fill: 0.5mm

Full Cure Time: 24 hours (with heat)
Pressure Rating: Up to 10,000 psi

Appearance : Clear blue liquid/gel

Odour : Characteristic - solvent

Specific Gravity : 1.2

Flammability : Flammable as a liquid/gel.

SAFETY PRECAUTIONS

Revision: 2 | Date: 23/05/2013

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

