



Granville

EP 85W/140

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville EP 85W/140 is a multigrade gear oil for heavy duty applications that has been formulated using a blend of quality base oils, the latest additive technology and extreme pressure additives to provide a gear oil that operates under the most severe of conditions.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5
MIL: MIL-L-2105 B, MIL-L-2105 C & MIL-L-2105 D
MAN: 342-Type M1 & 342-Type M2
ZF: TE-ML-05A, TE-ML-07A, TE-ML-08, TE-ML-12E, TE-ML-16B, TE-ML-16C, TE-ML-16D, TE-ML-17B, TE-ML-19B & TE-ML-21A

PRODUCT BENEFITS

- * Outstanding temperature control
- * Excellent anti corrosion properties
- * For heavy duty applications

PRODUCT USAGE

For manual gearboxes and axles where heavy duty service applications are required.

DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1637	5020618016373
5 Litre	1716	5020618017165
20 Litre	1714	5020618017141



Granville

EP 85W/140

1 Litre, 5 Litre & 20 Litre

SHELF LIFE

5 years from date of manufacture.

SPECIFICATION INFORMATION

API: GL5
MIL-L-2105B/C/D

Appearance : Amber liquid
Odour : Characteristic
Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	24	<32.5	28.59
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			406.43
Density	ASTM D792	@ 15°C			0.9

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

