Granville®
More than just an oil company

# TECHNICAL DATA

Revision: 1 | Date: 23/03/2012

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

# Autosol
# Roadster 40
## 5 Litre




* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|---|---|---|
| **5 Litre** | 0398 | 5020618003984 |

## PRODUCT DESCRIPTION

Autosol Roadster 40 is a traditional non detergent motor oil specifically for use in vintage and classic vehicle engines.

## RECOMMENDED FOR USE BY AUTOSOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SA
SAE: 40

## PRODUCT BENEFITS

* Suitable for vintage & classic cars
* Excellent wear protection

## PRODUCT USAGE

For engines where this specification lubricant is required.

## DIRECTIONS FOR USE

As recommended by the engine manufacturer.

## STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

## SHELF LIFE

5 years from date of manufacture.

| | | |
|---|---|---|
| **Appearance** | : | Amber liquid |
| **Odour** | : | Characteristic |
| **Solubility** | : | Insoluble in water |

HIGH PERFORMANCE
PREMIUM QUALITY

**Granville Oil & Chemicals Ltd.**
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

# Autosol
# Roadster 40
**5 Litre**

| Test | Method | Unit | Min. | Max. | Typical |
|---|---|---|---|---|---|
| Viscosity, Kinematic 100°c | ASTM D445 | $mm^2/s$ | 12.5 | <16.3 | 13.22 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.7 | | |
| Viscosity, Kinematic 40°c | ASTM D445 | $mm^2/s$ | | | 130.71 |
| Density | ASTM D792 | @ 15°c | | | 0.887 |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

HIGH PERFORMANCE
PREMIUM QUALITY

**Granville Oil & Chemicals Ltd.**
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com