

# Burgess Marine Woodsealer

500ml, 1 Litre, 2.5 Litre & 5 Litre

## PRODUCT DESCRIPTION

Burgess Marine Woodsealer is a waterborne acrylic emulsion with UV blocking inorganic pigments. When applied to timber Burgess Marine Woodsealer dries to form a microporous membrane, sealing the timber from the ravages of the environment whilst allowing the timber to breathe naturally. Originally developed for the marine market it has been consistently acclaimed by the Marine Press as being a quick and economical-to-apply sealer that meets the harsh demands of the marine environment. Ideal for use on all exterior wooden and plywood surfaces on a variety of vessels including Smacks, Bawleys and Clinker yachts. Also suitable for decking, strakes and capping rails etc. It contains UV blocking pigments which help to prevent degradation of wood by the sun's rays. Will not crack or craze like varnish.

Marine Woodsealer can be used either as a complete treatment leaving a matt finish or as a primer to be over coated with Burgess Marine Top Gloss or Marine Clearsealer.

## PRODUCT BENEFITS

- \* Quick drying
- \* Water based
- \* Allows timbers to breathe

## PRODUCT USAGE

Ideal for use on all exterior wooden and plywood surfaces on a variety of vessels including Smacks, Bawleys and Clinker yachts. Also suitable for decking, strakes and capping rails etc.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
500ml	0729	5020618007296
1 Litre	0752	5020618007524
2.5 Litre	0748	5020618007487
5 Litre	0749	5020618007494



# Burgess Marine Woodsealer

500ml, 1 Litre, 2.5 Litre & 5 Litre

## DIRECTIONS FOR USE

Timber to be coated should be free from all types of paint, varnish, wax, oil and grease. The surface may be damp but should be drying. Grey weathered wood need not be sanded. New or newly sanded oily woods (i.e. Teak) should be left to weather before application.

Burgess Marine Woodsealer can be applied by brush, spray or soft cloth and it is recommended to apply a minimum of two coats. However on very porous timber more coats may be required. Marine Woodsealer will normally dry in 15 minutes, however additional coats may be applied before each coat has dried.

An air temperature of 5°C - 30°C is preferred, but avoid applying the product if the relative humidity is greater than 80% or when there is a risk of rain or heavy condensation during the drying period. When applying in confined spaces ensure sufficient air movement is available to remove excess moisture released during the drying process.

Clean all brushes and spray equipment with clean water before the product dries.

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

## SHELF LIFE

2 years from date of manufacture if stored unopened in the original container in a frost-free environment.

## SPECIFICATION INFORMATION

Touch dry: 15 minutes

Coverage: 8m<sup>2</sup>/l (dependent upon absorbency of substrate)

**Appearance** : Golden brown opaque liquid

**Odour** : Mild perceptible odour

**Specific Gravity** : 1.04

**Solubility** : Miscible in water

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.



# Burgess Marine Woodsealer

500ml, 1 Litre, 2.5 Litre & 5 Litre

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.



**Granville Oil & Chemicals Ltd.**

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND

**Tel:** +44 (0)1709 890099 • [www.granvilleoil.com](http://www.granvilleoil.com)