

## Granville Hypalube Evo Fully Synthetic 5W/30

1 Litre & 5 Litre

### PRODUCT DESCRIPTION

Hypalube EVO 5W/30 fully synthetic long life has been formulated using high quality additives and base lubricants to produce a product with numerous long life applications. Hypalube EVO is suitable for use in vehicles requiring Low SAPS lubricant (Sulphated Ash, Phosphorus and Sulphur) where exhaust after treatment devices fitted.

Please refer to the vehicle handbook to ensure the required specification is covered.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2 & C3

BMW: LL-04

GM: LL-A-025, LL-B-025 & dexos 2

MB: 229.31, 229.51 & 229.52

API: SN

Porsche: C30

VW: 502.00, 504.00, 505.00, 505.01 & 507.00

Fiat: 9.55535-S3



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	K0923	5020618009238
5 Litre	K0924	5020618009245

### PRODUCT BENEFITS

- \* Fully Synthetic Formulation
- \* Long Life capabilities
- \* Protects engine at optimum temperature and performance
- \* For use with exhaust after treatment devices

### PRODUCT USAGE

Use as per the engine manufacturers recommendations

### DIRECTIONS FOR USE

Always Check for vehicle compatibility.



# Granville Hypalube Evo Fully Synthetic 5W/30

1 Litre & 5 Litre

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

## SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.07
Total Base Number	ASTM D2896	mg KOH/g	7		8.33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°C		-36	
NOACK Volatility	ASTM D5800	%		<10	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			59.81
Density	ASTM D792	@ 15°C			0.852

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

