Granville®
More than just an oil company

TECHNICAL DATA

Revision: 5 | Date: 11/12/2024

Slick 50
Engine Treatment
750ml



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
750ml	61399750	5026349014152

PRODUCT DESCRIPTION

Slick 50 Engine Treatment is a unique formula for all new or old petrol and diesel engines, including vehicles with turbo chargers and catalytic converters, that helps to extend engine life. Slick 50 Engine Treatment gives durable protection during successive oil changes, during tough stop/start driving and high temperature and high stress conditions thereby lowering the risk of costly engine repairs, re-builds and breakdowns..

PRODUCT BENEFITS

* Helps protect against friction and heat
* Sustains optimum performance
* Extends engine life
* Treats the engine not the oil
* Laboratory tested, road proven
* Compatible with all mineral & synthetic engine oils

PRODUCT USAGE

For engines up to 3000cc

DIRECTIONS FOR USE

Pour directly into engine. Do not overfill. If carrying out a full oil and filter change, drain oil and fit new filter. Refill with appropriate Granville engine oil, replacing 750ml of oil with the entire 750 ml contents of Slick 50 engine treatment. Run the engine then re-check the oil level and top up with Granville engine oil if necessary.

DOSAGE INFORMATION

Contents of 750ml Slick 50 Engine treatment will treat up to 3000 cc engines.

Re-treat after 20,000km. Re-treating after shorter intervals will not harm your engine.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Slick 50
Engine Treatment
750ml

STORAGE INSTRUCTIONS
Store sealed in a cool, dry place.

SHELF LIFE
3 years from date of manufacture.

SPECIFICATION INFORMATION
Suitable for use in Vehicles with Diesel Particulate filters.

Appearance	:	Amber oily liquid
Odour	:	Characteristic
Specific Gravity	:	0.865 - 0.889 @ 20°C
Solubility	:	Insoluble in water

SAFETY PRECAUTIONS
Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION
Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com