

## Granville Hypalube C2 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Granville Hypalube C2 5W/30 is a new generation, fully synthetic multi-grade engine oil formulated to meet the performance demands of low emission engines which combine high performance, fuel efficiency and emission control. Manufactured to a Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C2 oil.

It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used.

NOTE: This oil is NOT suitable for Vehicles that require Low Speed Pre-ignition (LSPI) capabilities. Suitable for vehicle up to 2017.



\* Image for illustrative purposes only.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2

PSA: B71 2290 (<2017)

API: SN/CF

SIZE	PART NO	BARCODE
1 Litre	0704	5020618007043
5 Litre	0705	5020618007050
20 Litre	0709	5020618007098
199 Litre	0708	5020618007081

### PRODUCT BENEFITS

\* Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation

\* Fully Synthetic

### PRODUCT USAGE

Use where recommended by the engine manufacturer

### DIRECTIONS FOR USE

Use as required by the engine manufacturer



# Granville Hypalube C2 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

## SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	11
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.9
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			67
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				156

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

