

TECHNICAL DATA

Granville MTF FS 75W

1Litre

PRODUCT DESCRIPTION

Granville MTF FS 75W is a quality fully synthetic manual transmission fluid that protects synchronisers in modern manual transmissions. If offers superior gear shift capabilities under severe conditions whilst giving the added benefit of being fuel efficient. Using selected additives ensures good low temperature performance, bearing and gear protection and fuel efficiency.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-4

VW: G 052 512, G 052 178, G 060 726 & G 052 726

BMW: MTF LT-3 Ford: WSS-M2C200-D2

VAG: G 052 171 & G 055 512



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|--------|---------|---------------|
| 1Litre | 1410 | 5020618014102 |

PRODUCT BENEFITS

- * Superior gear shift
- * Effective under severe conditions
- * Fuel efficient

DIRECTIONS FOR USE

Use as per the vehicle manufacturers recommendations

STORAGE INSTRUCTIONS

Store upright and sealed in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

Revision: 2 | Date: 12/05/2016





TECHNICAL DATA

Granville MTF FS 75W

1Litre

SPECIFICATION INFORMATION

Suitable for use in manual transmissions where the following specifications are required API: GL-4, BMW: MTF LT-3, Ford: WSS-M2C200-D2, VW: G 052 178, G 060 726, G 052 171, G 052 726 & G 052 512

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Flammability : >200°C

| Test | Method | Unit | Min. | Max. | Typical |
|------------------------------|-----------|--------|------|------|---------|
| Kinematic Viscosity at 100°c | ASTM D445 | mm²/s | 7 | <11 | 10.01 |
| Kinematic Viscosity at 40°c | ASTM D445 | mm²/s | | | 56.91 |
| Density | ASTM D792 | @ 15°c | | | 0.85 |

SAFETY PRECAUTIONS

Revision: 2 | Date: 12/05/2016

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

