

Veedol

Sintron C3 5W/30

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Veedol Sintron C3 5W-30 is a universal, synthetic, fuel economy motor oil developed according to the most recent technology. Formulated using specially selected synthetic base oils with high viscosity index and a well-balanced choice of advanced additives which helps achieve the following: improved fuel efficiency; high and shear stable viscosity index; excellent low temperature fluidity ensuring easy cold start; effective lubrication at very high temperatures; unique detergent/dispersion additive system ensuring engine cleanliness with negligible sludge; reduced formation of combustion ashes; very strong protection against wear, corrosion and foaming.

Veedol Sintron C3 5W-30 is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application range.

OEM APPROVALS

BMW: LL-04
MB-Approval: 229.51 & 229.52
VW: 505.00 & 505.01
GM: Dexos™ 2

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
API: SN

PRODUCT BENEFITS

- * OEM Approved product
- * Improved fuel efficiency
- ** Effective lubrication at very high temperatures



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|---------|---------|---------------|
| 1 Litre | 5000 | 5020618050001 |
| 5 Litre | 5001 | 5020618050018 |



Veedol

Sintron C3 5W/30

1 Litre & 5 Litre

PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

| | |
|-------------------|----------------------|
| Appearance | : Amber oily liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 12.195 |
| Total Base Number | ASTM D2896 | mg KOH/g | 10 | | |
| Pour Point | ASTM D97 | °C | | <-36 | |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.5 | | |
| NOACK Volatility | ASTM D5800 | % | | 10 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 69.55 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |
| Viscosity, CCS -30°C | ASTM D4684 | mPa.s | | 6600 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.





Granville[®]
More than just an oil company

TECHNICAL DATA

Revision: 2 | Date: 07/07/2017

Veedol Sintron C3 5W/30

1 Litre & 5 Litre

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com