

# TECHNICAL DATA

# Veedol Powertron Ultra 5W/40

1 Litre & 5 Litre

## **PRODUCT DESCRIPTION**

Veedol Powertron Ultra 5W-40 motor oil is developed according to the most recent technology and blended from specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained: high resistance against shearing; fast cold start; safe lubrication film at very high temperatures; reduced formation of combustion ashes;

very good detergency and dispersion; strong protection against wear, corrosion and foaming.

Veedol Powertron Ultra 5W-40 motor oil is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is suitable for use in petrol and diesel engines, with or without turbocharging. This product meets the requirements of several OEMs and thus has a wide application.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	5012	5020618050124
5 Litre	5013	5020618050131

### **OEM APPROVALS**

BMW: LL-04 MB-Approval: 229.51 VW: 505.00 & 505.01

#### RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3 API: SN/CF Fiat: 9.55535-S2 Ford: WSS-M2C917-A GM: Dexos<sup>™</sup> 2 MB: 229.31 & 226.5 Porsche: A40 Renault: RN0700 & RN0710



AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com



# TECHNICAL DATA

# Veedol Powertron Ultra 5W/40

1 Litre & 5 Litre

## **PRODUCT BENEFITS**

\* OEM Approved product

- \* Fast cold start
- \* Reduced formation of combustion ashes

### **PRODUCT USAGE**

Recommended for applications where this grade and specification of lubricant is required

#### **DIRECTIONS FOR USE**

Use as per the engine manufacturers handbook

#### **STORAGE INSTRUCTIONS**

Store sealed and upright in a cool dry place out of the reach of children

### SHELF LIFE

5 years from date of manufacture

Appearance	:	Amber oily liquid
Odour	:	Characteristic
Specific Gravity	:	0.85 @ 15.6°C (typical)
Solubility	:	Insoluble in water

#### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

#### **TRANSPORT CLASSIFICATION**

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com