

# Veedol

## Sintron C4 5W/30

1 Litre & 5 Litre

### PRODUCT DESCRIPTION

Veedol Sintron C4 5W-30 is a fuel economy, universal motor oil, developed according to the most recent technology and is blended with specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated: lower fuel consumption; suitable for modern catalysts; low combustion ash building (Low SAPS); fast cold start; safe lubrication film at high temperatures; very good detergency and dispersion with very strong protection against wear, corrosion and foaming.

Veedol Sintron C4 5W-30 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles for which the Renault specification RN0720 is required, which are equipped with modern three way catalysts and diesel particle filters. Due to its very Low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.

Warning: These oils have the lowest SAPS limits and may be unsuitable for use in some engines.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	5008	5020618050087
5 Litre	5009	5020618050094

### OEM APPROVALS

Renault: RN0720

### RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C4

MB: 226.51

### PRODUCT BENEFITS

- \* OEM Approved product
- \* Lower fuel consumption
- \* Very strong protection against wear, corrosion and foaming



# Veedol

## Sintron C4 5W/30

1 Litre & 5 Litre

### PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

### DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

### STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

### SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber oily liquid
<b>Odour</b>	: Characteristic
<b>Specific Gravity</b>	: 0.851 @ 15.6°C (typical)
<b>Solubility</b>	: Insoluble in water

### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

