

# Granville

## FS-FX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Granville FS-FX 0W/30 is a fully synthetic Mid SAPS engine oil specifically formulated to meet the requirements of the new generation Ford Dura Torq engines (2014>). This Mid SAPS formulation is also suitable for certain Alfa Romeo, Fiat, Hyundai, Jeep, Kia, Suzuki and Toyota engines where specified

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2  
Ford: WSS-M2C950-A  
Fiat: 9.55535-DS1 & 9.55535-GS1  
STJLR: .03.5007  
BMW: LL-12 FE

### PRODUCT BENEFITS

- \* Especially formulated for certain Ford engines
- \* Mid SAPS formulation
- \* Excellent wear and corrosion protection
- \* Superior fuel efficiency

### PRODUCT USAGE

For engines fitted with exhaust after treatment devices where this grade and specification is recommended

### DIRECTIONS FOR USE

Use as per the vehicle manufacturers recommendations



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0865	5020618008651
5 Litre	0866	5020618008668
20 Litre	0867	5020618008675
199 Litre	0872	5020618008729



# Granville

## FS-FX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place, out of the reach of children

### SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	:	Amber liquid
<b>Odour</b>	:	Characteristic
<b>Solubility</b>	:	Insoluble in water
<b>Percentage of Biodiesel</b>	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.6
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	7		9.8
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			60.4
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				169

### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

