

Granville Hypafleet E9 10W/40

5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hypafleet E9 10W/40 is a superior high performance heavy duty diesel engine oil that has been formulated using the latest additives and high quality synthetic base oils to produce a low SAPS (sulphated ash, Phosphorus and Sulphur) engine oil that is suitable for use with exhaust after treatment systems including DPF's and SCR/EGR NOX reducing systems. This engine oil is suitable for mixed fleet applications including Euro IV, V and VI engine types.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E6, E7 & E9
API: CJ-4
MAN: 3477 & 3271-1
MB: 228.51
MTU Type 3.1 & MTU Type 2.1
JASO: DH-2
Renault Truck: RLD-2 & RLD-3
Volvo: VDS-4
CAT: ECF-1-A, ECF-2 & ECF-3
Cummins: 20081
Scania: Low Ash
Iveco: 18-809 Class NG2
Detroit Diesel: 93K218
DEUTZ: DQC IV-10 & DQC IV-18 LA
Mack: EO-OPP & EO-NPP

PRODUCT BENEFITS

- *Low SAPS (sulphated ash, Phosphorus and Sulphur)
- *Excellent level of engine protection
- *High level of soot management.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
5 Litre	6429	5020618064299
20 Litre	6430	5020618064305
199 Litre	6432	5020618064329



Granville Hypafleet E9 10W/40

5 Litre, 20 Litre & 199 Litre

PRODUCT USAGE

For use in engines where this grade and specification is required.

DIRECTIONS FOR USE

Use in accordance with the manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and keep out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water



Granville Hypafleet E9 10W/40

5 Litre, 20 Litre & 199 Litre

Percentage of Base Oil : 76.00%

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.5	<16.3	14.93
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.87
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	3.9		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			99.93
Density	ASTM D792	@ 15°C			0.859

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

