

# Granville Hypafleet E7 20W/50

20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Hypalube Hypafleet E7 20W/50 is a wide ranging heavy duty engine oil suitable for use in commercial, agricultural and off-highway applications. The combination of quality additives and superior base oils make this oil suitable for use in Euro 1 to Euro 5 engines including those fitted with exhaust after treatment devices.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E7  
API: CI-4 & SL  
MAN: 3275  
MB: 228.3  
CAT: ECF-2  
Cummins: CES 20077 & CES 20078  
Mack: EO-M+ & EO-N  
MTU Type 2  
Renault Truck: RLD-2  
Volvo: VDS-3  
Detroit Diesel: 93K215  
DEUZ: DQC III



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6493	5020618064930
199 Litre	6495	5020618064954

## PRODUCT BENEFITS

- \*For use in mixed fleet applications
- \*Quality base oils and additives for superior protection
- \*High level of wear protection and heat control

## PRODUCT USAGE

For use where this grade and specification of engine oil is required

## DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations



# Granville Hypafleet E7 20W/50

20 Litre & 199 Litre

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and out of the reach of children

## SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: 80.00%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	16.3	<21.9	
Viscosity, CCS -15°C	ASTM D4684	mPa.s		9500	
Total Base Number	ASTM D2896	mg KOH/g	10		
Pour Point	ASTM D97	°C		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		12	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

