

Granville Hypafleet E7 20W/50

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hypafleet E7 20W/50 is a wide ranging heavy duty engine oil suitable for use in commercial, agricultural and off-highway applications. The combination of quality additives and superior base oils make this oil suitable for use in Euro 1 to Euro 5 engines including those fitted with exhaust after treatment devices.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E7
API: CI-4 & SL
MAN: 3275
MB: 228.3
CAT: ECF-2
Cummins: CES 20077 & CES 20078
Mack: EO-M+ & EO-N
MTU Type 2
Renault Truck: RLD-2
Volvo: VDS-3
Detroit Diesel: 93K215
DEUTZ: DQC III

PRODUCT BENEFITS

- *For use in mixed fleet applications
- *Quality base oils and additives for superior protection
- *High level of wear protection and heat control

PRODUCT USAGE

For use where this grade and specification of engine oil is required

DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6493	5020618064930
199 Litre	6495	5020618064954



Granville Hypafleet E7 20W/50

20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: 80.00%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	16.3	<21.9	
Viscosity, CCS -15°C	ASTM D4684	mPa.s		9500	
Total Base Number	ASTM D2896	mg KOH/g	10		
Pour Point	ASTM D97	°C		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		12	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

