

# Granville Hy-Vis Hydraulic 32

5 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Hypalube Hy-vis 32 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603

David Brown: S1.53.101

Denison Filterability: TP02100

DIN: 51524 Part 2 (HLP)

Vickers: 1.286.S & 1.286.S3



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

\*Excellent pumpability

\*Protects against oxidation and corrosion.

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and out of the reach of children

## SHELF LIFE

5 years from date of manufacture

**Appearance** : Amber liquid

SIZE	PART NO	BARCODE
5 Litre	0182	5020618001829
20 Litre	0723	5020618007234
199 Litre	0132	5020618001324



# Granville Hy-Vis Hydraulic 32

5 Litre, 20 Litre & 199 Litre

**Odour** : Characteristic  
**Solubility** : Insoluble in water  
**Percentage of Biodiesel** : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	28.8	35.2	32.57
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s			5.54
Density	ASTM D792	@ 15°C			0.871

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

