

# Granville Hy-Vis Hydraulic 46

20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Hyalube Hy-vis 46 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603  
David Brown: S1.53.101  
Denison Filterability: TP02100  
DIN: 51524 Part 2 (HLP)  
Vickers: 1.286.S & 1.286.S3  
ISO: 6734-4 HM

## PRODUCT BENEFITS

- \*Excellent pumpability
- \*Protects against oxidation and corrosion.

## STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

## SHELF LIFE

5 years from date of manufacture

**Appearance** : Amber liquid



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	0724	5020618007241
199 Litre	0140	5020618001409



# Granville Hy-Vis Hydraulic 46

20 Litre & 199 Litre

**Odour** : Characteristic  
**Solubility** : Insoluble in water  
**Percentage of Biodiesel** : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	41.4	50.6	46.65
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s			6.88
Density	ASTM D792	@ 15°C			0.877

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

