

Granville Hy-Vis Hydraulic 68

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hy-Vis 68 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603

David Brown: S1.53.101

Denison Filterability: TP02100

DIN: 51524 Part 2 (HLP)

Vickers: 1.286.S & 1.286.S3



* Image for illustrative purposes only.

PRODUCT BENEFITS

*Excellent pumpability

*Protects against oxidation and corrosion.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 20 Litre | 0725 | 5020618007258 |
| 199 Litre | 0009 | 5020618000099 |

STORAGE INSTRUCTIONS

Store Upright and sealed in a cool place and out of the reach of children

SHELF LIFE

5 Years from date of manufacture

Appearance : Amber liquid



Granville Hy-Vis Hydraulic 68

20 Litre & 199 Litre

Odour : Characteristic
Solubility : Insoluble in water
Percentage of Biodiesel : Nil

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|-----------|--------------------|------|------|---------|
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | 61.2 | 74.8 | 67.64 |
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | | | 8.79 |
| Density | ASTM D792 | @ 15°C | | | 0.874 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

