

Granville

FS-RX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville FS-RX 5W/30 is a high performance fully synthetic engine oil formulated for the latest Renault engines. This Mid SAPS oil is suitable for use in turbo charged petrol direct injection engines, Euro 6 diesel engines and is safe to use with vehicles fitted with exhaust emission after treatment devices. FS-RX 5W/30 offers excellent soot control and component protection.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3

Renault: RN17



* Image for illustrative purposes only.

PRODUCT BENEFITS

Mid SAPS formulation

Controls heat build up within the engine

Suitable for Euro 6 diesel engines

PRODUCT USAGE

For engines where this grade and specification is recommended.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed and upright in a cool dry place out of the reach of children.

SIZE	PART NO	BARCODE
1 Litre	1178	5020618011781
5 Litre	1179	5020618011798
20 Litre	1180	5020618011804
199 Litre	1181	5020618011811



Granville

FS-RX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.3
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			75.6
Density	ASTM D792	@ 15°C			0.85
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7.5		10.6
HTHS Viscosity	ASTM D4683	mPa.s	>3.5		
NOACK Volatility	ASTM D5800	%		<11	
Viscosity Index	ASTM D2270				161

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

