



10k

Engine Stop Leak

375ml & 375ml Norwegian

PRODUCT DESCRIPTION

10K Boost Engine Stop Leak is formulated to help stop leaks caused by seals and gaskets that can shrink or even crack. It will help to expand and revitalise all rubber engine oil seals, including rear main seals, crankshaft oil seals, timing cover seals etc. Important - will not treat mechanically defective or non-rubber gaskets.

PRODUCT BENEFITS

Prevents expensive repairs.
Will revitalise rubber gaskets & seals.
Prevents loss of oil.

PRODUCT USAGE

Add to engine oil and drive vehicle in the normal manner.

DIRECTIONS FOR USE

Park vehicle on a level surface.
Pour contents of can into engine oil filler. Ensure that you do not over fill, always check the dipstick level.

DOSAGE INFORMATION

Contents of can will treat between 3-6 litres of engine oil.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

3 years from date of manufacture.

Appearance : Amber liquid
Odour : Characteristic
Solubility : Soluble in motor oil



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
375ml	1430	5020618014300
375ml Norwegian	1687	N/A



10k
Engine Stop Leak
375ml & 375ml Norwegian

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s			12.54
Density	ASTM D792	@ 15°C			0.88

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

