Granville
EP 75W/85
1 Litre



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1721	5020618017219

PRODUCT DESCRIPTION

Granville EP 75W/85 is a fully synthetic GL-5 gear & axle oil manufactured using high quality base oils and the latest in additive technology to provide a lubricant that has outstanding wear protection whilst offering protection under high shock/load, high torque and high speeds. Ep75W/85 is highly effective in controlling heat build up within the components.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5
Fiat: 9.55550-MZ9, 9.55550-DA3 & 9.55550-DA9
MB: 235.31, 239.71 & 235.62
VW: G 052 190 & G 052 518
Volvo: 97312
Chrysler: MS-9070

PRODUCT BENEFITS

* Fully Synthetic.
* Excellent heat control properties.
* Effective Wear protection.

DIRECTIONS FOR USE

Use as recommended by the vehicle manufaturer.

STORAGE INSTRUCTIONS

Store sealed and upright in a cool, dry place and out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
EP 75W/85
1 Litre

Odour : Characteristic

Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	11	<13.5	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com