

TECHNICAL DATA

Granville Copper Grease

20g Tube, 70g Tube, 500g Tin, 3kg & 70g Norwegian

PRODUCT DESCRIPTION

Granville Copper Anti-Seize Compound is a soft copper coloured grease used to prevent seizure caused by metal to metal contact under arduous conditions. The product is both thermally and mechanically stable, very water repellent and will naturally adhere to metal surfaces.

Ensures excellent protection for metal parts against heat, seizure, rust, corrosion, water and acid.

PRODUCT BENEFITS

- * Extremely long lasting
- * Assists in assembly and dismantling
- * Non melting
- * Excellent corrosion inhibitor
- * Extremely stable, both mechanically & thermally

PRODUCT USAGE

Copper Grease is recommended for most applications where metal to metal contact needs to be avoided and for all assembly work where ease of dismantling is required including; keys, keyways, track adjusters and many more industrial and automotive uses. Copper Grease is especially recommended for applications where lead content is unacceptable (present in many other anti-seize compounds).

DIRECTIONS FOR USE

Apply grease to the required surfaces to the recommended amount.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.



* Image for illustrative purposes only.

| | SIZE | PART NO | BARCODE |
|---|---------------|---------|---------------|
| | 20g Tube | 0151 | 5020618001515 |
| | 70g Tube | 0148 | 5020618001485 |
| I | 500g Tin | 0149 | 5020618001492 |
| | 3kg | 0155 | 5020618001553 |
| | 70g Norwegian | 1699 | N/A |



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com



TECHNICAL DATA

Granville Copper Grease

20g Tube, 70g Tube, 500g Tin, 3kg & 70g Norwegian

SHELF LIFE

5 years from date of manufacture.

SPECIFICATION INFORMATION

- * Operating temperature range: -30°C to +1100°C
- * Melting point: None (infusible product)
- * Worked penetration: 280-320mm
- * Un-worked penetration @ 25°C: 265-295mm
- * NLGI classification: 2
- * Co-efficient of friction: 0.11

| Appearance | : | Gold/Copper smooth grease |
|------------|---|---------------------------|
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com