

Granville Bearing Fit & Studlock

10ml & 50ml

PRODUCT DESCRIPTION

Granville Bearing Fit and Studlock is a fast curing, high strength anaerobic thread locking compound for bonding and sealing threads and retaining cylindrical parts. Bearing Fit & Studlock is highly resistant to heat, vibration, water, gases, oils, hydrocarbons and many other chemicals. The product is removable with normal hand tools.

PRODUCT BENEFITS

- * Locks transmission and engine block studs, valve sets etc.
- * Ideal for fasteners up to 25mm diameters
- * High strength, permanent and eliminates need for double nutting and welding
- * Prevents corrosion and leakage

DIRECTIONS FOR USE

Surface should be dry, clean and free of any contamination. Bearing Fit & Studlock should be applied to the bolt in sufficient quantity to fill threads. Bearing Fit & Studlock performs best in thin bond gaps.

DO NOT return any unused material to the original packaging.
DO NOT allow the product to come into contact with with plastics.

STORAGE INSTRUCTIONS

Anaerobic adhesive shall be ideally stored in a cool, dry place in unopened containers at a room temperature between 5°C to 25°C.

SHELF LIFE

2 years from date of manufacture.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
10ml	3114	5020618031147
50ml	3096	5020618030966



Granville Bearing Fit & Studlock

10ml & 50ml

SPECIFICATION INFORMATION

Operating temperature range: -55°C to 150°C
Handling cure time: 10 minutes
Functional cure time: 1-3 hours
Full cure time: 24 hours
Maximum diameter of thread/gap filling: 0.15mm
Breakaway strength: 28 Newton Meter (N.m)

Appearance : Red methacrylate ester

Odour : Characteristic

Specific Gravity : 1.11

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

