

Granville Jack Oil 500ml

PRODUCT DESCRIPTION

Granville Jack Oil is a fully inhibited hydraulic oil developed specifically for use in hydraulic trolley and bottle jacks. Jack Oil has been specifically formulated to alleviate slow system response and sponginess.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ISO: 32 & VG22

PRODUCT BENEFITS

* Prevents slow response & sponginess

PRODUCT USAGE

Developed specifically for use for use in hydraulic trolley and bottle jacks.

DIRECTIONS FOR USE

As per the manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
500ml	0177	5020618001775





Granville Jack Oil

500ml

Odour : Characteristic
Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	28.8	35.2	32.4
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s			5.8
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				120

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

