Granville

Hypalube C1 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Hypalube C1 5W/30 has been formulated using the very latest additives to produce a fuel efficient engine oil that offers the ultimate protection for exhaust emission after treatment devices requiring a low SAPS (sulphated ash, phosphorous and sulphur) engine oil.
It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C1
Ford: WSS-M2C934-B
JASO: DL-1
STJLR: .03.5005

SIZE	PART NO	BARCODE
1 Litre	0671	5020618006718
5 Litre	0672	5020618006725
20 Litre	0676	5020618006763
199 Litre	0675	5020618006756

PRODUCT BENEFITS

* Low SAPS (sulphated ash, phosphorous and sulphur)formulation
* Fully Synthetic

PRODUCT USAGE

To be used where specified by the engine manufacturer

DIRECTIONS FOR USE

Use as per the engine manufacturer's recommendations

STORAGE INSTRUCTIONS

Store sealed in a cool dry place out of the reach of children

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Hypalube C1 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	11.4
Viscosity, CCS -30°c	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.6
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			67.8
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				160

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com