Granville

FS-BX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville FS-BX 0W/30 is the very latest generation fully synthetic low viscosity engine oil. FS-BX offers excellent fuel efficiency and engine protection whilst meeting the requirements of soot control for those vehicles with engine exhaust after treatment devices fitted.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
BMW: LL-04 & LL-19 FE
MB: 229.51
Porsche: C30
VW: 504.00, 507.00, 503.00, 506.00 & 506.01
API: SN

SIZE	PART NO	BARCODE
1 Litre	0793	5020618007937
5 Litre	0794	5020618007944
20 Litre	0795	5020618007951
199 Litre	0799	5020618007999

PRODUCT BENEFITS

* Low SAPS formulation
* Fully synthetic
* Excellent fuel efficiency

PRODUCT USAGE

For vehicles where this grade and specification of engine oil is required.

DIRECTIONS FOR USE

Use as specified by the vehicle manufacturer

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

FS-BX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	:	Amber oily liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	11.5
Viscosity, CCS -35°c	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		10.4
Pour Point	ASTM D97	°c		-42	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			64.2
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				175

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com