# Veedol

# Powertron Ultra 5W/40

**1 Litre & 5 Litre**

## PRODUCT DESCRIPTION

Veedol Powertron Ultra 5W-40 motor oil is developed according to the most recent technology and blended from specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained: high resistance against shearing; fast cold start; safe lubrication film at very high temperatures; reduced formation of combustion ashes;
very good detergency and dispersion; strong protection against wear, corrosion and foaming.
Veedol Powertron Ultra 5W-40 motor oil is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEMs and thus has a wide application.

* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|---|---|---|
| **1 Litre** | 5012 | 5020618050124 |
| **5 Litre** | 5013 | 5020618050131 |

## OEM APPROVALS

BMW: LL-04
MB-Approval: 229.51
VW: 505.00 & 505.01

## RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
API: SN/CF
Fiat: 9.55535-S2
Ford: WSS-M2C917-A
GM: Dexos™ 2
MB: 229.31 & 226.5
Porsche: A40
Renault: RN0700 & RN0710

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

**Granville Oil & Chemicals Ltd.**
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

# Veedol

# Powertron Ultra 5W/40

**1 Litre & 5 Litre**

## PRODUCT BENEFITS

* OEM Approved product
* Fast cold start
* Reduced formation of combustion ashes

## PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

## DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

## SHELF LIFE

5 years from date of manufacture

| | | |
|---|---|---|
| **Appearance** | : | Amber oily liquid |
| **Odour** | : | Characteristic |
| **Specific Gravity** | : | 0.85 @ 15.6°C (typical) |
| **Solubility** | : | Insoluble in water |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

**Granville Oil & Chemicals Ltd.**
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com