Granville®
More than just an oil company

TECHNICAL DATA

Revision: 3 | Date: 07/07/2017

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Veedol

Sintron Longlife III 5W/30

1 Litre & 5 Litre

* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Veedol Sintron Longlife III 5W-30 is a fuel economy, universal motor oil developed according to the most recent technology. It is blended with specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties: lower fuel consumption; Mid SAPS content; suitable for modern catalysts; fast cold start; safe lubrication film at high temperatures; extended oil drain intervals, very good detergency and dispersion; strong protection against wear, corrosion and foaming.
Veedol Sintron Longlife III 5W-30 is a specially formulated motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the latest VW 504.00/507.00 requirements, in practice, also called VW Longlife III oils.

SIZE	PART NO	BARCODE
1 Litre	5004	5020618050049
5 Litre	5005	5020618050056

OEM APPROVALS

BMW: LL-04
MB-Approval: 229.51
Porsche: C30
VW: 504.00 & 507.00

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
API: SN

PRODUCT BENEFITS

* OEM Approved product
* Lowers fuel consumption
* Excellent protection against wear & corrosion

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Veedol

Sintron Longlife III 5W/30

1 Litre & 5 Litre

PRODUCT USAGE

Recommended for applications were this grade and specification of lubricant is required

DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	:	Amber oily liquid
Odour	:	Characteristic
Specific Gravity	:	0.85 @ 15.6°C (typical)
Solubility	:	Insoluble in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com